

Customized Solutions

The need for extended reach tools is steadily increasing as operators try to maximize production and extend lateral lengths. The **Casing XRV** can be customized to meet your operational requirements and is available with a drillable insert. Typically run on intermediate casing strings, the insert would be drilled out with other float equipment. The Casing XRV can accommodate any thread sizes, weight, and grade.

Connections	2 3/8" Hydrill 511	2 7/8" AB ST-L	3 1/2" Hydrill 511	3 1/2" AB TC 11	4 1/2" Buttress	4 1/2" LTC	4 1/2" TMK DQX	5 1/2" LTC	5 1/2" Buttress	5 1/2" TMK DQX	7" Buttress
Tool Size (OD)	2.38"	2.90"	3.50"	3.84"	5.00"	5.00"	5.00"	6.05"	6.05"	6.09"	7.66"
Total Length	1.29'	1.54'	1.68'	1.71'	2.18'	2.32'	5.73'	2.91'	2.83'	5.16'	2.96'
Weight (lbs)	14 lbs	22 lbs	34 lbs	34 lbs	101 lbs	106 lbs	248 lbs	182 lbs	180 lbs	310 lbs	339 lbs
Available Flow Range (gpm)	42-100	100-150	100-200	100-200	100-500	100-500	100-500	100-600	100-600	100-600	200-1000
Temp Range	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited
Operating Frequency	10-14 hz	10-14 hz	10-14 hz	10-14 hz	10-14 hz	10-14 hz	10-14 hz	10-14 hz	10-14 hz	10-14 hz	10-14 hz
Pressure Drop (psi)	300-600	300-600	300-600	300-600	300-600	300-600	300-600	300-600	300-600	300-600	300-600

Chart indicates off-the-shelf inventory. * Additional connections and tool sizes available on request. Tool lengths and ODs are approximate.



Applications

- Extended Laterals
- Deviated Wellbores
- Liner Hanger Systems
- Cemented or Non-Cemented
- Open-Hole Packer Systems
- Sleeve-Systems



A Division of Thru Tubing Solutions

Mid-Continent Region 405.378.5450 | Southwest Region 432.288.9052 | Appalachian Region 412.787.4600
 Rocky Mountain Region 701.420.1040 | Canada 780.986.0807